



DESCRIPTION OF THE CALET CALIBRATION FILES

Version 1

DATE 20 Jan 2022

Prepared by:
Lorella Angelini (HEASARC)

CHANGE RECORD PAGE (1 of 1)

DOCUMENT TITLE : Description of the CALET Calibration files			
ISSUE	DATE	PAGES AFFECTED	DESCRIPTION
Version 1	20 Jan 2022	all	First version

Table of Contents

1	Introduction	4
1.1	Scope.....	4
1.2	References.....	4
1.3	Acronyms.....	5
2	CALET Calibration File Set.....	6
2.1	File Naming Convention.....	6
2.2	Directory structure	6
2.3	Datatype	7
3	General file description Calibration File Set	7
3.1	Mandatory Keywords.....	7
4	Specific File format.....	10
4.1	CGBM : EBOUNDS for PH and EVENT modes.....	10
4.2	CGBM : EBOUNDS for TH.....	19

1 Introduction

This document describes the format of CALET Calibration Files in the CALibration DataBase (CALDB). CALDB includes the results obtained from the analysis of the in orbit data. The results are stored in the OGIP CALDB structure in the FITS file format, adhering in principle to the standard OGIP format. These files are recorded in CALDB for archival purposes and they are used in the CALET data analysis by end-users. The files required by the pipeline processing are not included.

The CALET calibration files are produced by the CALET team at different institutes in Japan and delivered to the HEASARC.

1.1 Scope

This document provides a naming convention and header structure for the calibration files with a brief description.

1.2 References

[1] - BCF & CPF Calibration File Guidelines - OGIP Calibration Memo CAL/GEN/92-003

[2] - HFWG Recommendation R8 -1994 February 02

[3] - Required and Recommended FITS keywords for Calibration Files -OGIP Calibration Memo CAL/GEN/92-011

1.3 Acronyms

ARF	Ancillary Response File
BCF	Basic Calibration File
CALDB	Calibration Database
CIF	Calibration File
CPF	Calibration Product File
FITS	Flexible Image Transport System
GSFC	Goddard Space Flight Center
HDU	Header Data Unit
HEASARC	High Energy Astrophysics Science Archive Research Center
HFWD	High Energy FITS Working Group
HK	House-Keeping
OGIP	Office of the Guest Investigator Programs
PHA	Pulse Height Amplitude
PI	Pulse Invariant
PSF	Point Spread Function
QE	Quantum Efficiency
RMF	Redistribution Matrix File

2 CALET Calibration File Set

The chapter lists the naming convention for the CALDB files and the different calibration type products stored in CALDB.

2.1 File Naming Convention

The filename convention is the following:

<mi>_<det>_<datatype>_[<date>]vxxx.ext

where:

mi is a 4 digit string that identifies the mission and instrument. Note usually the first digits are just for the mission however to not introduce different convention of the file in the archive the identify both mission and instrument. This is set to :

- cgbm for CALET GBM
- ccal for CALET Calorimeter

The **det** identify the detector used stored in the keyword DETNAM. The string are : instrument The mission identifier string is set to 'ca' named after CALET.

- 'hx1', 'hx2', 'hxm' for the GBM HXM1 and HXM2 or both HXM respectively;
- 'sgm' for the GBM SGM
- 'chd' for the Calorimeter
- 'gen' for files applicable to all instruments unless noted.

These strings are used in the filenames of CALDB and science files.

datatype is the calibration data type identifier. The string should describe the file content unambiguously within 8 characters long. Underscores or mathematical symbols are not allowed. Longer strings may be considered on case by case basis, but they are strongly discouraged;

date is an integer giving the date when the file should first be used, with the format: YYYYMMDD;

version is three digits integer giving the file issue number, ex 001;

ext is set to 'fits' for all files with the following exceptions: 'rmf' or 'rsp' is used for the redistribution matrix and 'arf' is used for the ancillary response files.

2.2 Directory structure

The CALDB of CALET is divided in the following directories :

```

    /calet
    /gen          /ccal          /cgbm          .....
    /bcf /cpf /index  /bcf   /cpf   /index  /bcf /cpf /index
    /... /.../...  /.../.../...
    
```

The /gen directory contains files that are applicable to all instruments. The /cgbm directory contains files that are related to the detector HXM1/ HXM2 and SGM part of the CGBM. The /ccal directory contains files related to the calorimeter and subsystem detector.

Each instrument directory is subdivided in /bcf and /cpf containing the basic and high level calibration file. Both the /bcf and /cpf are divided in subdirectories each dedicated to a subgroup of file type.

2.3 Datatype

Table 2.3 contains a summary of all the different type of calibration files :

Datatype	Caldb directory	Description
ebphall	cpf	Ebounds for the PH mode low/high gain for GBM
ebvtall	cpf	Ebounds for the EVENT mode low/high gain for GBM
ebthlow	cof	Ebounds for the TH low gain for GBM
ebthhig	cpf	Ebounds for the TH high gain for GBM
rsp cgbm hxmi		TBD
rsp cgbm hxm2		TBD
rsp cgbm sgm		TBD

Table 2.1 -Datatypes and short description of CALET files

3 General file description Calibration File Set

All CALET calibration files are FITS files. Keywords required by FITS OGIP standards and listed in this chapter are described in documents [1], [2] and [3] (see references in Section 1). Chapters 4 gives the exact strings used in the CALDB keywords for CALET calibration files as well as a description of different FITS-file format.

3.1 Mandatory Keywords

Table 3.1a lists the mandatory keywords added to the primary and to the headers of all extensions of the Calibration FITS files. Remarks on specific comments are added in italics.

Keyword name	Keyword value	Comment
TELESCOP	'CALET'	/Telescope (mission) name
INSTRUME	<instrument>	/Instrument Name
DETNAM	<detector name>	/Detector Name (<i>HXM, HX1, HX2, SGM, ASC, CHD</i>)
DATAMODE	<datamode>	/Datamode
DATE	YYYY-MM-DDThh:mm:ss	/Creation Date
CHECKSUM	<up to date checksum>	/HDU checksum updated <date>
DATASUM	<up to date datasum>	/Data unit checksum updated <date>

Table 3.1a -Mandatory keywords for all extensions

Table 3.1b lists the additional mandatory keywords common to all table headers. Each CALDB keyword has different values for different Calibration Files. The values for the CALDB and the EXTNAME keywords are specified for each datatype in the chapter dedicated to each of the instruments.

Table 3.1b		
Keyword name	Keyword value	Comment
EXTNAME	<extension name>	/Name of the binary table extension <i>or</i> /Name of the image extension This is omitted if data are stored in the Primary Header
ORIGIN	<organization name>	/ Source of FITS file
CALDB keywords:		
CCLSxxxx	OGIP-class of calibration file	/Dataset is a Calibration Product File /Dataset is a Basic Calibration File
CDTPxxxx	<datatype code>	/Calibration file contains data
CCNMxxxx	<extension codename>	/Type of Calibration data
CDESxxxx	<descriptive string>	/ Description
CVSDxxxx	<start valid data>	/UTC date when file should first be used
CVSTxxxx	<start valid time>	/UTC time when file should first be used
CBDnxxxx	Array describing parameter limitations of the dataset	/Parameter boundaries
Additional keywords		
TDIMnnn	Number of elements & Ordering of n -d array	/Array dimensions
HUCLASS	'OGIP '	/Format conforms to OGIP standards (Only when applicable)
HUCLAS n	<character string to classify the extension	/(Specific to the type) (Only when applicable)

Table 3.1b – Mandatory header keywords for all extensions that contains calibration data

The keywords content in Table 3.1a and 3.1b are described in the section dedicated to each of the data file.

The "CBDnxxx" keyword that should be used to differentiate otherwise identical extensions in a file. The first CBD keyword should be named CBD10001, the second CBD20001, etc... All CBD keywords should follow the syntax "KEYWORD (SELECTION)" where "keyword" is the quantity on which a selection is done. The "TDIM" keywords is only necessary for array with 2 or more axis and the HUCLAS* family only when applicable.

The keywords in Table 3.1c are the minimum mandatory if the binary table contains columns related to time. Additional keywords may be necessary and are listed in the section dedicated to each of the data file.

Table 3.1c		
Keyword name	Keyword value	Comment
TIMESYS	TT	/Time system
MJDREFI	51544	/MJD reference 2000-01-01 00:00:00 UTC
MJDREFF	7.4287037037037E-04	/MJD reference (fractional of day)
CLOCKAPP	T	/If clock corrections are applied (F/T)

Table 3.1c– Mandatory timing keywords for all extensions with time columns

The content for the keywords INSTRUME, DETNAM, and DATAMODE are listed in the following tables. These strings are also used in the science data files.

Table 3.1d		
Keyword Name	Keyword String	Explanation (not FITS comment)
GBM		
INSTRUME	CGBM	Indicate the CALET GBM
DETNAM	HXM	DETNAM is set to HXM if the calibration or the science files contains information valid for both HXM. The keyword is set to HXM1 or HXM2 if the calibration or science data are for the HXM1 or HXM2 respectively.
	HXM1	
	HXM2	
	SGM	For the SGM part of the GBM
	ASC	For optical sky monitor
	ALL	Set to ALL to indicate that files are applicable to SGM and HXM1/2
DATAMODE	PH_LOW	For the PH mode low gain
	PH_HIGH	For the PH mode high gain
	PH	For the PH mode low or high gain
	TH_LOW	For the TH mode low gain
	TH_HIGH	For the TH mode high gain
	TH	For the TH mode low or high gain
	EVENT	For the event mode regardless if in high or low gain
	EVENT_LOW	For the event mode in low gain
	EVENT_HIGH	For the event mode in high
	IMAGE	For the image mode of the ASC
CALORIMETER		
INSTRUME	CCAL	Indicate the CALET Calorimeter .
DETNAM	CHD	For the Charge Detector

Table 3.1d – Values for CALET INSTRUME, DETNAM and DATAMODE

4 Specific File format

4.1 CGBM : EBOUNDS for PH and EVENT modes

These files contain the boundary energy values for the channels for the PH and EVENT mode data. Each file has the following structure: empty primary header , 1st extension for the low gain data and 2nd for the high gain data. Since the HXM1 and HXM2 has the same boundary only one caldb file is created applicable for both. The filenames are :

Filename	Description
cgbm_hxm_ebphall_YYYYMMNNvxxx.fits	Containing the ebounds for the PH mode low and high gain of the HXM1 and HXM2
cgbm_sgm_ebphall_YYYYMMNNvxxx.fits	Containing the ebounds for the PH mode low and high gain of the SGM
cgbm_hxm_ebevtall_YYYYMMNNvxxx.fits	Containing the ebounds for the EVENT mode low and high gain of the HXM1 and HXM2
cgbm_sgm_ebevtall_YYYYMMNNvxxx.fits	Containing the ebounds for the EVENT mode low and high gain of the SGM

All four files have an empty primary header and two extensions one for the low gain and one for the high gain. The following tables contain the header for each of the files. Table 4.1a list the header for the PH mode high and low gain for the (file cgbm_hxm_ebphall_YYYYMMNNvxxx.fits) :

Table 4.1a		
<i>EBOUNDS : Structure primary header HXM PH high or low gain data</i>		
Keyword	Value	Comment
TELESCOP	'CALET'	/Telescope mission name
INSTRUME	'CGBM'	/Instrument name
DETNAM	'HXM'	/ Detector subsystem
ORIGIN	'JAXA, WCOC'	/Origin of the FITS file
DATE	'yyyy-mm-ddThh:mm:ss'	/File creation date
CREATOR	'string'	/Software that create 1 st the file
CHECKSUM	'value'	/ data unit checksum updated date
DATASUM	'value'	/ HDU checksum updated date
<i>EBOUNDS : Structure 1st extension PH low gain data for the HXM</i>		
Keyword	Value	Comment
EXTNAME	'EBOUNDS'	/name of the HDU
TTYPER1	'CHANNEL'	/Detector channel number
TFORM1	'I'	/data format of field
TUNIT1	'chan'	/physical unit of field
TTYPER2	'E MIN'	/Low energy bounds
TFORM2	'1E'	/data format of field
TUNIT2	'keV'	/physical unit of field
TTYPER3	'E MAX'	/High energy bounds
TFORM3	'1E'	/data format of field
TUNIT3	'keV'	/physical unit of field
TLMIN1	0	/Minimum legal value
TLMAX1	409	/Maximum legal value
TELESCOP	'CALET'	/Telescope mission name
INSTRUME	'CGBM'	/Instrument name
DETNAM	'HXM'	/ Detector
DATAMODE	'PH LOW'	/Data mode
CCLS0001	'CPF'	/Dataset is a Calibration Product File
CDTP0001	'DATA'	/Calibration file contains data
CCNM0001	'EBOUNDS'	/Type of Calibration data
CDES0001	'Energy Channel boundary for HXM PH LOW data '	/ Description
CVSD0001	'2000-01-01'	/UTC date when file should first be used
CVST0001	'00:00:00'	/UTC time when file should first be used
CBD10001	'GAIN(LOW)'	/Parameter Boundary
CBD20001	'DATAMODE(PH LOW)'	/Parameter Boundary
HUCLASS	'OGIP'	/ format conforms to OGIP standard
HUCLAS1	'RESPONSE'	/ <hduclass1>
HUCLAS2	'EBOUNDS'	/ <hduclas2>
HUVERS	'1.2.0'	/Keyword information for Caltools Software
HUVERS1	'1.1.0'	/Obsolete
HUVERS2	'1.2.0'	/Obsolete
RMFVERSN	'1992a'	/Obsolete
FILTER	'none'	/Filter in use (if any)

CHANTYPE	'PI'	/No corrections have been applied
DETCANS	410	/Total number of PHA channels
PI2ENE	0.75	/Conversion PI to energy
ORIGIN	'JAXA, WCOC'	/Origin of the fits file
CREATOR	'string'	/Software that create 1 st the file
DATE	'yyyy-mm-ddThh:mm:ss'	/File creation date
CHECKSUM	'value'	/ data unit checksum updated date
DATASUM	'value'	/ HDU checksum updated date
EBOUNDS : Structure 2nd extension PH high gain data for the HXM		
Keyword	Value	Comment
EXTNAME	'EBOUNDS'	/name of the HDU
TTYPE1	'CHANNEL'	/Detector channel number
TFORM1	'I'	/data format of field
TUNIT1	'chan'	/physical unit of field
TTYPE2	'E MIN'	/Low energy bounds
TFORM2	'IE'	/data format of field
TUNIT2	'keV'	/physical unit of field
TTYPE3	'E MAX'	/High energy bounds
TFORM3	'IE'	/data format of field
TUNIT3	'keV'	/physical unit of field
TLMIN1	0	/Minimum legal value
TLMAX1	101	/Maximum legal value
TELESCOP	'CALET'	/Telescope mission name
INSTRUME	'CGBM'	/Instrument name
DETNAM	'HXM'	/ Detector
DATAMODE	'PH HIGH'	/Data mode
CCLS0001	'CPF'	/Dataset is a Calibration Product File
CDTP0001	'DATA'	/Calibration file contains data
CCNM0001	'EBOUNDS'	/Type of Calibration data
CDES0001	'Energy Channel boundary. HXM PH HIGH'	/ Description
CVSD0001	'2000-01-01'	/UTC date when file should first be used
CVST0001	'00:00:00'	/UTC time when file should first be used
CBD10001	'GAIN(HIGH)'	/Parameter Boundary
CBD20001	'DATAMODE(PH HIGH)'	/Parameter Boundary
HDUCLASS	'OGIP'	/ format conforms to OGIP standard
HDUCLAS1	'RESPONSE'	/<hduclass1>
HDUCLAS2	'EBOUNDS'	/ <hduclas2>
HDUVERS	'1.2.0'	/Keyword information for Caltools Software
HDUVERS1	'1.1.0'	/Obsolete
HDUVERS2	'1.2.0'	/Obsolete
RMFVERSN	'1992a'	/Obsolete
FILTER	'none'	/Filter in use (if any)
CHANTYPE	'PI'	/No corrections have been applied
DETCANS	102	/Total number of PHA channels
PI2ENE	0.024	/Conversion PI to energy
ORIGIN	'JAXA, WCOC'	/Origin of the fits file
CREATOR	'string'	/Software that create 1 st the file
DATE	'yyyy-mm-ddThh:mm:ss'	/File creation date

CHECKSUM	'value'	/ data unit checksum updated date
DATASUM	'value'	/ HDU checksum updated date

Table 4.1a – Format for the HXM PH mode ebounds

Table 4.1b list the header for the ebounds file of the PH mode high and low gain for the SGM (file cgbm_sgm_ebphall_YYYYMMNNvxxx.fits) :

Table 4.1b		
<i>EBOUNDS : Structure primary header SGM PH high or low gain data</i>		
Keyword	Value	Comment
TELESCOP	'CALET'	/Telescope mission name
INSTRUME	'CGBM'	/Instrument name
DETNAM	'SGM'	/ Detector subsystem
ORIGIN	'JAXA, WCOC'	/Origin of the FITS file
DATE	'yyyy-mm-ddThh:mm:ss'	/File creation date
CREATOR	'string'	/Software that create 1 st the file
CHECKSUM	'value'	/ data unit checksum updated date
DATASUM	'value'	/ HDU checksum updated date
<i>EBOUNDS : Structure 1st extension PH low gain data for the SGM</i>		
Keyword	Value	Comment
EXTNAME	'EBOUNDS'	/name of the HDU
TTYPE1	'CHANNEL'	/Detector channel number
TFORM1	'I'	/data format of field
TUNIT1	'chan'	/physical unit of field
TTYPE2	'E MIN'	/Low energy bounds
TFORM2	'1E'	/data format of field
TUNIT2	'keV'	/physical unit of field
TTYPE3	'E MAX'	/High energy bounds
TFORM3	'1E'	/data format of field
TUNIT3	'keV'	/physical unit of field
TLMIN1	0	/Minimum legal value
TLMAX1	409	/Maximum legal value
TELESCOP	'CALET'	/Telescope mission name
INSTRUME	'CGBM'	/Instrument name
DETNAM	'SGM'	/ Detector
DATAMODE	'PH LOW'	/Data mode
CCLS0001	'CPF'	/Dataset is a Calibration Product File
CDTP0001	'DATA'	/Calibration file contains data
CCNM0001	'EBOUNDS'	/Type of Calibration data
CDES0001	'Energy Channel boundary for SGM PH LOW data '	/ Description
CVSD0001	'2000-01-01'	/UTC date when file should first be used
CVST0001	'00:00:00'	/UTC time when file should first be used
CBD10001	'GAIN(LOW)'	/Parameter Boundary
CBD20001	'DATAMODE(PH LOW)'	/Parameter Boundary
HDUCLASS	'OGIP'	/ format conforms to OGIP standard
HDUCLAS1	'RESPONSE'	/ \langle hduclass1 \rangle
HDUCLAS2	'EBOUNDS'	/ \langle hduclas2 \rangle
HDUVERS	'1.2.0'	/Keyword information for Caltools Software
HDUVERS1	'1.1.0'	/Obsolete
HDUVERS2	'1.2.0'	/Obsolete
RMFVERSN	'1992a'	/Obsolete
FILTER	'none'	/Filter in use (if any)

CHANTYPE	'PI'	/No corrections have been applied
DETCANS	410	/Total number of PHA channels
PI2ENE	7.	/Conversion PI to energy
ORIGIN	'JAXA, WCOC'	/Origin of the fits file
CREATOR	'string'	/Software that create 1 st the file
DATE	'yyyy-mm-ddThh:mm:ss'	/File creation date
CHECKSUM	'value'	/ data unit checksum updated date
DATASUM	'value'	/ HDU checksum updated date
EBOUNDS : Structure 2nd extension PH high gain data for the SGM		
Keyword	Value	Comment
EXTNAME	'EBOUNDS'	/name of the HDU
TTYPE1	'CHANNEL'	/Detector channel number
TFORM1	'I'	/data format of field
TUNIT1	'chan'	/physical unit of field
TTYPE2	'E MIN'	/Low energy bounds
TFORM2	'IE'	/data format of field
TUNIT2	'keV'	/physical unit of field
TTYPE3	'E MAX'	/High energy bounds
TFORM3	'IE'	/data format of field
TUNIT3	'keV'	/physical unit of field
TLMIN1	0	/Minimum legal value
TLMAX1	102	/Maximum legal value
TELESCOP	'CALET'	/Telescope mission name
INSTRUME	'CGBM'	/Instrument name
DETNAM	'SGM'	/ Detector
DATAMODE	'PH HIGH'	/Data mode
CCLS0001	'CPF'	/Dataset is a Calibration Product File /Dataset is a Basic Calibration File
CDTP0001	'DATA'	/Calibration file contains data
CCNM0001	'EBOUNDS'	/Type of Calibration data
CDES0001	'Energy Channel boundary. SGM PH HIGH data'	/ Description
CVSD0001	'2000-01-01'	/UTC date when file should first be used
CVST0001	'00:00:00'	/UTC time when file should first be used
CBD10001	'GAIN(HIGH)'	/Parameter Boundary
CBD20001	'DATAMODE(PH HIGH)'	/Parameter Boundary
HUCLASS	'OGIP'	/ format conforms to OGIP standard
HUCLAS1	'RESPONSE'	/ <hduclass1>
HUCLAS2	'EBOUNDS'	/ <hduclas2>
HUVERS	'1.2.0'	/Keyword information for Caltools Software
HUVERS1	'1.1.0'	/Obsolete
HUVERS2	'1.2.0'	/Obsolete
RMFVERSN	'1992a'	/Obsolete
FILTER	'none'	/Filter in use (if any)
CHANTYPE	'PI'	/No corrections have been applied
DETCANS	102	/Total number of PHA channels
PI2ENE	0.23	/Conversion PI to energy
ORIGIN	'JAXA, WCOC'	/Origin of the fits file
CREATOR	'string'	/Software that create 1 st the file

DATE	'yyyy-mm-ddThh:mm:ss'	/File creation date
CHECKSUM	'value'	/ data unit checksum updated date
DATASUM	'value'	/ HDU checksum updated date

Table 4.1b – Format for the SGM PH mode ebounds

Table 4.1c list the header for the EVENT mode high and low gain for the ebound file for the SGM and HXM (file `cgbm_sgm_ebeval_YYYYMMNNvxxx.fits` `cgbm_hxm_ebeval_YYYYMMNNvxxx.fits`). The keywords DETNAM, PI2ENE and CDES0001 (marked red in table 4.1c) have to be set correctly for the SGM or HXM files.

Table 4.1c		
<i>EBOUNDS : Structure primary header EVENT high or low gain data</i>		
Keyword	Value	Comment
TELESCOP	'CALET'	/Telescope mission name
INSTRUME	'CGBM'	/Instrument name
DETNAM	'XXX'	/ Detector subsystem
ORIGIN	'JAXA, WCOC'	/Origin of the FITS file
DATE	'yyyy-mm-ddThh:mm:ss'	/File creation date
CREATOR	'string'	/Software that create 1 st the file
CHECKSUM	'value'	/ data unit checksum updated date
DATASUM	'value'	/ HDU checksum updated date
<i>EBOUNDS : Structure 1st extension EVENT low gain data for the HXM /SGM (see DETNAM)</i>		
Keyword	Value	Comment
EXTNAME	'EBOUNDS'	/name of the HDU
TTYPE1	'CHANNEL'	/Detector channel number
TFORM1	'I'	/data format of field
TUNIT1	'chan'	/physical unit of field
TTYPE2	'E MIN'	/Low energy bounds
TFORM2	'1E'	/data format of field
TUNIT2	'keV'	/physical unit of field
TTYPE3	'E MAX'	/High energy bounds
TFORM3	'1E'	/data format of field
TUNIT3	'keV'	/physical unit of field
TLMIN1	0	/Minimum legal value
TLMAX1	4095	/Maximum legal value
TELESCOP	'CALET'	/Telescope mission name
INSTRUME	'CGBM'	/Instrument name
DETNAM	'XXX'	/ Detector
DATAMODE	'EVENT LOW'	/Data mode
CCLS0001	'CPF'	/Dataset is a Calibration Product File
CDTP0001	'DATA'	/Calibration file contains data
CCNM0001	'EBOUNDS'	/Type of Calibration data
CDES0001	'Energy Channel boundary for XXX EVENT LOW data '	/ Description
CVSD0001	'2000-01-01'	/UTC date when file should first be used
CVST0001	'00:00:00'	/UTC time when file should first be used
CBD10001	'GAIN(LOW)'	/Parameter Boundary
CBD20001	'DATAMODE(EVENT LOW)'	/Parameter Boundary
HDUCLASS	'OGIP'	/ format conforms to OGIP standard
HDUCLAS1	'RESPONSE'	/<hduclass1>
HDUCLAS2	'EBOUNDS'	/ <hduclas2>
HDUVERS	'1.2.0'	/Keyword information for Caltools Software
HDUVERS1	'1.1.0'	/Obsolete
HDUVERS2	'1.2.0'	/Obsolete
RMFVERSN	'1992a'	/Obsolete
FILTER	'none'	/Filter in use (if any)

CHANTYPE	'PI'	/No corrections have been applied
DETCANS	4095	/Total number of PHA channels
PI2ENE	XXX	/Conversion PI to energy
ORIGIN	'JAXA, WCOC'	/Origin of the fits file
CREATOR	'string'	/Software that create 1 st the file
DATE	'yyyy-mm-ddThh:mm:ss'	/File creation date
CHECKSUM	'value'	/ data unit checksum updated date
DATASUM	'value'	/ HDU checksum updated date
EBOUNDS : Structure 2nd extension EVENT high gain data for the HXM /SGM (see DETNAM)		
Keyword	Value	Comment
EXTNAME	'EBOUNDS'	/name of the HDU
TTYPE1	'CHANNEL'	/Detector channel number
TFORM1	'I'	/data format of field
TUNIT1	's'	/physical unit of field
TTYPE2	'E MIN'	/Low energy bounds
TFORM2	'1E'	/data format of field
TUNIT2	'keV'	/physical unit of field
TTYPE3	'E MAX'	/High energy bounds
TFORM3	'1E'	/data format of field: 2-byte INTEGER
TUNIT3	'keV'	/physical unit of field
TLMIN1	0	/Minimum legal value
TLMAX1	4095	/Maximum legal value
TELESCOP	'CALET'	/Telescope mission name
INSTRUME	'CGBM'	/Instrument name
DETNAM	'XXX'	/ Detector
DATAMODE	'EVENT HIGH'	/Data mode
CCLS0001	'CPF'	/Dataset is a Calibration Product File
CDTP0001	'DATA'	/Calibration file contains data
CCNM0001	'EBOUNDS'	/Type of Calibration data
CDES0001	'Energy Channel boundary for the XXX EVENT HIGH'	/ Description
CVSD0001	'2000-01-01'	/UTC date when file should first be used
CVST0001	'00:00:00'	/UTC time when file should first be used
CBD10001	'GAIN(HIGH)'	/Parameter Boundary
CBD20001	'DATAMODE(EVENT HIGH)'	/Parameter Boundary
HDUCLASS	'OGIP'	/ format conforms to OGIP standard
HDUCLAS1	'string'	/ <hduclas1>
HDUCLAS2	'string'	/ <hduclas2>
HDUVERS	'1.2.0'	/Keyword information for Caltools Software
HDUVERS1	'1.1.0'	/Obsolete
HDUVERS2	'1.2.0'	/Obsolete
RMFVERSN	'1992a'	/Obsolete
FILTER	'none'	/Filter in use (if any)
CHANTYPE	'PI'	/No corrections have been applied
DETCANS	4096	/Total number of PHA channels
PI2ENE	XXX	/Conversion PI to energy
ORIGIN	'JAXA, WCOC'	/Origin of the fits file
CREATOR	'string'	/Software that create 1 st the file
DATE	'yyyy-mm-ddThh:mm:ss'	/File creation date

CHECKSUM	'value'	/ data unit checksum updated date
DATASUM	'value'	/ HDU checksum updated date

Table 4.1c – Format for the HXM/SGM EVENT mode ebounds

4.2 CGBM : EBOUNDS for TH

These files contain the boundary energy values for the channels of TH mode. Each file has the following structure: empty primary header, 1st extension for the low or high gain data. Since the HXM1 and HXM2 has the same boundary only one caldb file is created applicable for both. The filenames are :

Filename	Description
cgbm_hxm_ebthall_YYYYMMNNvxxx.fits	Containing the ebounds for the TH mode low and high gain of the HXM1 and HXM2
cgbm_sgm_ebthall_YYYYMMNNvxxx.fits	Containing the ebounds for the TH mode low and high gain of the SGM

The CALET data in TH mode are binned in four energy bands in low and high gain. The energy intervals for each of the four energy bands may change with time. These values are saved in a time dependent CALDB file that contains an empty primary header, 1st extension for the high gain and second extension for the low gain. Each row contains three columns: TIME , E_MIN and E_MAX. The E-Min and E_MAX are vectors contains 4 values defining the four energy bands. The validity of these energy bands start from the time written in the column until the time of the next row.

There is one file for the HXM and one file for the SGM and Table 4.2a and 4.2b describe the headers for the two files.

Table 4.2b		
<i>Energy boundaries : Structure primary header SGM TH high or low gain data</i>		
Keyword	Value	Comment
TELESCOP	'CALET'	/Telescope mission name
INSTRUME	'CGBM'	/Instrument name
DETNAM	'HXM'	/ Detector subsystem
ORIGIN	'JAXA, WCOC'	/Origin of the FITS file
DATE	'yyyy-mm-ddThh:mm:ss'	/File creation date
CREATOR	'string'	/Software that create 1 st the file
CHECKSUM	'value'	/ data unit checksum updated date
DATASUM	'value'	/ HDU checksum updated date
<i>EBOUNDS : Structure 1st extension PH low gain data for the SGM</i>		
Keyword	Value	Comment
EXTNAME	'ENERGY BOUNDS'	/name of the HDU
TTYPER1	'TIME'	/Detector channel number
TFORM1	'1D'	/data format of field
TUNIT1	's'	/physical unit of field
TTYPER2	'E MIN'	/Low energy bounds
TFORM2	'4I'	/data format of field
TUNIT2	'keV'	/physical unit of field
TTYPER3	'E MAX'	/High energy bounds
TFORM3	'4E'	/data format of field
TUNIT3	'keV'	/physical unit of field
TTYPER4	'TH CHAN'	/TH channel number
TFORM4	'4E'	/data format of field
TTYPER5	'ADC MIN CHAN'	/Original ADC min channel
TFORM5	'4E'	/data format of field
TTYPER6	'ADC MAX CHAN'	/Original ADC max channel
TFORM6	'4E'	/data format of field
TELESCOP	'CALET'	/Telescope mission name
INSTRUME	'CGBM'	/Instrument name
DETNAM	'HXM'	/ Detector
DATAMODE	'TH LOW'	/Data mode
DATE-OBS	'yyyy-mm ddThh:mm:ss'	/Start Date
DATE-END	'yyyy-mm ddThh:mm:ss'	/Stop Date
TSTART	0.0	/Start time
TSTOP	0.0	/Start Time
MJDREFI	51544	/MJD reference day 01 Jan 2000 00:00:00
MJDREFF	7.4287037037037E-04	/MDJ reference (fraction of day)
TIMEREFR	'LOCAL'	/Reference Frame
TASSIGN	'SATELLITE'	/Time assigned
TIMESYS	'TT'	/ Time System
TIMEUNIT	' s'	/Time unit for timing header keywords
CLOCKAPP	T	/ If clock correction are applied (F/T)
CCLS0001	'CPF'	/Dataset is a Calibration Product File

CDTP0001	'DATA'	/Calibration file contains data
CCNM0001	'ENERGY BOUND'	/Type of Calibration data
CDES0001	'Energy Channel boundary for SGM TH LOW data'	/Description
CVSD0001	'2000-01-01'	/UTC date when file should first be used
CVST0001	'00:00:00'	/UTC time when file should first be used
CBD10001	'GAIN(LOW)'	/Parameter Boundary
CBD20001	'DATAMODE(TH LOW)'	/Parameter Boundary
ORIGIN	'JAXA, WCOC'	/Origin of the fits file
CREATOR	'string'	/Software that create 1 st the file
DATE	'yyyy-mm-ddThh:mm:ss'	/File creation date
CHECKSUM	'value'	/data unit checksum updated date
DATASUM	'value'	/ HDU checksum updated date
EBOUNDS : Structure 2nd extension PH high gain data for the SGM		
Keyword	Value	Comment
EXTNAME	'ENERGY BOUNDS'	/name of the HDU
TTYE1	'TIME'	/Detector channel number
TFORM1	'ID'	/data format of field
TUNIT1	's'	/physical unit of field
TTYE2	'E MIN'	/Low energy bounds
TFORM2	'4I'	/data format of field
TUNIT2	'keV'	/physical unit of field
TTYE3	'E MAX'	/High energy bounds
TFORM3	'4E'	/data format of field: 2-byte INTEGER
TUNIT3	'keV'	/physical unit of field
TTYE4	'TH CHAN'	/TH channel number
TFORM4	'4E'	/data format of field
TTYE5	'ADC MIN CHAN'	/Original ADC min channel
TFORM5	'4E'	/data format of field
TTYE6	'ADC MAX CHAN'	/Original ADC max channel
TFORM6	'4E'	/data format of field
TELESCOP	'CALET'	/Telescope mission name
INSTRUME	'CGBM'	/Instrument name
DETNAM	'HXM'	/ Detector
DATAMODE	'TH HIGH'	/Data mode
DATE-OBS	'yyyy-mm ddThh:mm:ss'	/Start Date
DATE-END	'yyyy-mm ddThh:mm:ss'	/Stop Date
TSTART	0.0	/Start time
TSTOP	0.0	/Start Time
MJDREFI	51544	/MJD reference day 01 Jan 2000 00:00:00
MJDREFF	7.4287037037037E-04	/MDJ reference (fraction of day)
TIMEREFS	'LOCAL'	/Reference Frame
TASSIGN	'SATELLITE'	/Time assigned
TIMESYS	'TT'	/ Time System
TIMEUNIT	's'	/Time unit for timing header keywords
CLOCKAPP	T	/ If clock correction are applied (F/T)
CCLS0001	'CPF'	/Dataset is a Calibration Product File
CDTP0001	'DATA'	/Calibration file contains data
CCNM0001	'ENERGY BOUND'	/Type of Calibration data

CDES0001	'Energy Channel boundary for SGM TH HIGH data '	/ Description
CVSD0001	'2000-01-01'	/UTC date when file should first be used
CVST0001	'00:00:00'	/UTC time when file should first be used
CBD10001	'GAIN(HIGH)'	/Parameter Boundary
CBD20001	'DATAMODE(TH_HIGH)'	/Parameter Boundary
ORIGIN	'JAXA, WCOC'	/Origin of the fits file
CREATOR	'string'	/Software that create 1 st the file
DATE	'yyyy-mm-ddThh:mm:ss'	/File creation date
CHECKSUM	'value'	/ data unit checksum updated date
DATASUM	'value'	/ HDU checksum updated date

Table 4.2a – Format for the HXM TH mode ebounds

Table 4.2b		
<i>Energy boundaries : Structure primary header SGM TH high or low gain data</i>		
Keyword	Value	Comment
TELESCOP	'CALET'	/Telescope mission name
INSTRUME	'CGBM'	/Instrument name
DETNAM	'SGM'	/ Detector subsystem
ORIGIN	'JAXA, WCOC'	/Origin of the FITS file
DATE	'yyyy-mm-ddThh:mm:ss'	/File creation date
CREATOR	'string'	/Software that create 1 st the file
CHECKSUM	'value'	/ data unit checksum updated date
DATASUM	'value'	/ HDU checksum updated date
<i>EBOUNDS : Structure 1st extension PH low gain data for the SGM</i>		
Keyword	Value	Comment
EXTNAME	'ENERGY BOUNDS'	/name of the HDU
TTYPE1	'TIME'	/Detector channel number
TFORM1	'1D'	/data format of field
TUNIT1	's'	/physical unit of field
TTYPE2	'E MIN'	/Low energy bounds
TFORM2	'4I'	/data format of field
TUNIT2	'keV'	/physical unit of field
TTYPE3	'E MAX'	/High energy bounds
TFORM3	'4E'	/data format of field: 2-byte INTEGER
TUNIT3	'keV'	/physical unit of field
TTYPE4	'TH CHAN'	/TH channel number
TFORM4	'4E'	/data format of field
TTYPE5	'ADC MIN CHAN'	/Original ADC min channel
TFORM5	'4E'	/data format of field
TTYPE6	'ADC MAX CHAN'	/Original ADC max channel
TFORM6	'4E'	/data format of field
TELESCOP	'CALET'	/Telescope mission name
INSTRUME	'CGBM'	/Instrument name
DETNAM	'SGM'	/ Detector
DATAMODE	'TH LOW'	/Data mode
DATE-OBS	'yyyy-mm ddThh:mm:ss'	/Start Date
DATE-END	'yyyy-mm ddThh:mm:ss'	/Stop Date
TSTART	0.0	/Start time
TSTOP	0.0	/Start Time
MJDREFI	51544	/MJD reference day 01 Jan 2000 00:00:00
MJDREFF	7.4287037037037E-04	/MDJ reference (fraction of day)
TIMeref	'LOCAL'	/Reference Frame
TASSIGN	'SATELLITE'	/Time assigned
TIMESYS	'TT'	/ Time System
TIMEUNIT	' s'	/Time unit for timing header keywords
CLOCKAPP	T	/ If clock correction are applied (F/T)
CCLS0001	'CPF'	/Dataset is a Calibration Product File

CDTP0001	'DATA'	/Calibration file contains data
CCNM0001	'ENERGY BOUND'	/Type of Calibration data
CDES0001	'Energy Channel boundary for SGM TH LOW data '	/ Description
CVSD0001	'2000-01-01'	/UTC date when file should first be used
CVST0001	'00:00:00'	/UTC time when file should first be used
CBD10001	'GAIN(LOW)'	/Parameter Boundary
CBD20001	'DATAMODE(TH LOW)'	/Parameter Boundary
ORIGIN	'JAXA, WCOC'	/Origin of the fits file
CREATOR	'string'	/Software that create 1 st the file
DATE	'yyyy-mm-ddThh:mm:ss'	/File creation date
CHECKSUM	'value'	/ data unit checksum updated date
DATASUM	'value'	/ HDU checksum updated date
EBOUNDS : Structure 2nd extension PH high gain data for the SGM		
Keyword	Value	Comment
EXTNAME	'ENERGY BOUNDS'	/name of the HDU
TTYE1	'TIME'	/Detector channel number
TFORM1	'ID'	/data format of field
TUNIT1	's'	/physical unit of field
TTYE2	'E MIN'	/Low energy bounds
TFORM2	'4I'	/data format of field
TUNIT2	'keV'	/physical unit of field
TTYE3	'E MAX'	/High energy bounds
TFORM3	'4E'	/data format of field: 2-byte INTEGER
TUNIT3	'keV'	/physical unit of field
TTYE4	'TH CHAN'	/TH channel number
TFORM4	'4E'	/data format of field
TTYE5	'ADC MIN CHAN'	/Original ADC min channel
TFORM5	'4E'	/data format of field
TTYE6	'ADC MAX CHAN'	/Original ADC max channel
TFORM6	'4E'	/data format of field
TELESCOP	'CALET'	/Telescope mission name
INSTRUME	'CGBM'	/Instrument name
DETNAM	'SGM'	/ Detector
DATAMODE	'TH HIGH'	/Data mode
DATE-OBS	'yyyy-mm ddThh:mm:ss'	/Start Date
DATE-END	'yyyy-mm ddThh:mm:ss'	/Stop Date
TSTART	0.0	/Start time
TSTOP	0.0	/Start Time
MJDREFI	51544	/MJD reference day 01 Jan 2000 00:00:00
MJDREFF	7.4287037037037E-04	/MDJ reference (fraction of day)
TIMEREFS	'LOCAL'	/Reference Frame
TASSIGN	'SATELLITE'	/Time assigned
TIMESYS	'TT'	/ Time System
TIMEUNIT	' s'	/Time unit for timing header keywords
CLOCKAPP	T	/ If clock correction are applied (F/T)
CCLS0001	'CPF'	/Dataset is a Calibration Product File
CDTP0001	'DATA'	/Calibration file contains data
CCNM0001	'ENERGY BOUND'	/Type of Calibration data

CDES0001	'Energy Channel boundary for SGM TH HIGH data '	/ Description
CVSD0001	'2000-01-01'	/UTC date when file should first be used
CVST0001	'00:00:00'	/UTC time when file should first be used
CBD10001	'GAIN(HIGH)'	/Parameter Boundary
CBD20001	'DATAMODE(TH_HIGH)'	/Parameter Boundary
ORIGIN	'JAXA, WCOC'	/Origin of the fits file
CREATOR	'string'	/Software that create 1 st the file
DATE	'yyyy-mm-ddThh:mm:ss'	/File creation date
CHECKSUM	'value'	/ data unit checksum updated date
DATASUM	'value'	/ HDU checksum updated date

Table 4.2a – Format for the SGM TH mode ebounds