



dssetattr

June 2, 2019

Abstract

Set/Add an attribute This task is part of the daltools package

1 Instruments/Modes

Instrument	Mode
------------	------

2 Use

3 Description

Set/Add an attribute

This task either updates an attribute with the given value/unit/label or creates a new attribute. The attribute name must be given in fully qualified notation. It is therefore possible to set an attribute in a dataset, block or column. The value is passed into the task as a string, where it is parsed, and converted to a value of the specified type.

4 Parameters

This section documents the parameters recognized by this task (if any).

Parameter	Mand	Type	Default	Constraints
label	no	String		

Comment to associate with the attribute

to	yes	String		
----	-----	--------	--	--

Fully qualified name of the attribute to be set

type	yes	String	string	
------	-----	--------	--------	--



Data type of the attribute's value

units	no	String		
--------------	----	--------	--	--

Units to associate with the attribute

value	yes	String		
--------------	-----	--------	--	--

Value of the attribute

5 Errors

This section documents warnings and errors generated by this task (if any). Note that warnings and errors can also be generated in the SAS infrastructure libraries, in which case they would not be documented here. Refer to the index of all errors and warnings available in the HTML version of the SAS documentation.

6 Input Files

- 1.


7 Output Files

- 1.

8 Algorithm

9 Comments

-



10 Future developments

References